



SS220

EXTERNAL DOME HOUSINGS

Attractive and compact indoor/outdoor fixed camera dome housing.

The SS220 housing has been designed for general purpose installations where aesthetic appeal is important. Access to the camera is via the front acrylic cover. The cover is attached to the main housing by three M4 pan philips screws.

A versatile camera mounting bracket allows the correct pan tilt positioning of the camera lens.

OPTIONS

Two wall mount brackets and a pendant adaptor are available for the housings. Custom droppers should provide a 1" B.S.P. female socket for pendant adaptors to thread into.

Wall brackets are designed to be used with SEE Security standard pole and corner mount adaptors.

PTZ minidome compatible options are available, allowing a common enclosure for installations where combinations of fixed and PTZ units are used. Tamper switches and lens liners are available as options.

Refer to Mounting Guide on page 37, Dropper Kits on page 35 and Housing Dimensions on page 41.

APPLICATIONS

Designed for mounting off walls or directly from the ceiling.

SPECIFICATIONS

Construction

1.6mm stainless steel.

Finish

Polished stainless steel outer body, black texture polyester powder coat on underside and interior of body.

Lens

3.0mm acrylic.

Cable Entry

Through wall brackets and adaptors.

Access

M4 pan philips.

Max. Camera Size

180mm. Maximum possible camera length will be dependant on angle of view required.

Weight

SS220- 3.45kg.



SS220

PART NUMBER	DESCRIPTION
SS220T	220mm stainless steel weatherproof dome with tinted lens.
SS220C	220mm stainless steel weatherproof dome with clear lens.
TSW SASS220	Tamper switch to suit SA220 & SS220 housings only.