



LPAR480

ENVIRONMENTAL HOUSING

IP66 Outdoor camera housing for general purpose applications.

Available in a powder coated zincanneal for general purpose use. The LPAR range of housings are designed to accommodate 1/4" to 1/3" CCD camera fitted with fixed and zoom lenses. There is a 100mm clear space behind the camera for connections when the maximum camera lens combination is used.

OPTIONS

The HDWMB3 and HDMPT2 wall bracket and manual pan tilt are the only standard mounting hardware available for the housing. These mounting brackets and pan tilts available as optional extras and are not included in the price of the housing.

Refer to Mounting Guide on page 36 and Housing Dimensions on page 40.

APPLICATIONS

Mounted off poles, building walls or in factories. Also ideal for use in mines.

SPECIFICATIONS

Construction

1.6mm zincanneal body and sun shield.

Finish

Mossvale sands (light beige) polyester powder coat.

Lens

4.8mm arris edged safety glass. Optional MR10 lexan.

Cable Entry

2 x 20mm PVC cable compression glands and 2 blanking grommets.

Access

2 x Southco stainless steel rotary clasps at the rear of the lid.

Electrical

Optional heater thermostat 24VAC 50Hz 11watts. Fan 24VAC 50Hz 3.2 watts.

Max. Camera Size

371 mm (L) x 178mm (W) at the camera platform reducing to 151 mm at the inside top of the lid x 140 mm (H). 170 mm height available without the camera sled.

Weight

LPAR480- 8.9kg.



LPAR480

PART NUMBER	DESCRIPTION
LPAR480	External housing complete with wall mount bracket and manual pan tilt bracket.
FANHTR480	Fan heater to suit LPAR480 housings.
TSW	Tamper switch to suit ECO & LPAR series housings.