

# ECOSS

## Environmental Housing



IP66 Outdoor camera housing for general purpose applications. The ECROSS housing is designed to accommodate 1/4" to 1/3" CCD cameras fitted with fixed and zoom lenses. The camera lens combination, up to the recommended maximum length, allows at least 100mm clear space behind the camera for connections.

The pivoting lid swings clear of the lens to allow camera access and set up with the cover open. In this design the installer has full access to the sides, top and rear of the camera and lens. The camera is mounted on a clamped plate for fast install and removal.

### Options

A pole mount adaptor, tamper switch, demister heater and fan are optional with the ECROSS housing.

ECO Housing is also available and comes in powder coated zinc anneal (ECO) for economy and powder coated 304 stainless steel (ECOSS) finish for corrosive environments.

### Applications

Mounted off poles, building walls or in factories. The ideal economical robust general-purpose camera housing.

### Specifications

<b>CONSTRUCTION</b>	1.6mm stainless steel
<b>FINISH</b>	White polyester powder coat
<b>LENS</b>	6.00mm arris edged glass
<b>CABLE ENTRY</b>	3 x 20mm entries, two in the base and one positioned at the rear of the housing
<b>ACCESS</b>	3 x 6mm pan head screws
<b>ELECTRICAL</b>	Optional heater thermostat 24 VAC 50Hz 11watts. Fan 24VAC 50Hz 3.2 watts
<b>MAX CAMERA SIZE</b>	220mm (L) x 115mm (W) x 86mm (H)
<b>WEIGHT</b>	4.7kg
<b>IP RATING</b>	IP66
<b>INCLUDED</b>	Manual Pan Tilt and Wall Mount Bracket

