

CMDH

INTERNAL DOME HOUSINGS



Interior surface mount dome housing for on-ceiling applications.

Stylish surface mount aluminium back box and trim ring dome housing allows a professional finish for on ceiling installations without the excessive size required for acrylic dome only to cover the camera and bracket.

The CMDH is designed to accept the standard RMLINER which hides camera position and has the added benefit of a rotating 360 degree lens. This allows the lens to be repositioned should it become damaged in the viewing area. This option provides an economic alternative to painted lenses.

OPTIONS

When ordering place 'C' for clear or 'T' for tinted at the end of the part number. eg: CMDHT. A tinted housing will be supplied should a preference not be stated.

Refer to housing Dimensions on page 42.

APPLICATIONS

The CMDH is ideal for on-ceiling applications where recessing is not an option and reduced installation costs are important.

SPECIFICATIONS

Construction

1.2mm aluminium.

Finish

Ceiling white exterior and black texture interior polyester powder coat.

Lens

3.0mm acrylic dome in clear or 332 tint.

Access

3 x M4 pan head screws.

Max. Camera Size

190mm.

Weight

CMDH- 1.8kg.



CMDH

PART NUMBER	DESCRIPTION
CMDHT	250mm on-ceiling mounted dome enclosure with clear lens.
CMDHC	250mm on-ceiling mounted dome enclosure with tinted lens.
RM LINER	250mm aluminium liner with viewing slot.
CMSK	Security kit. 33 x post button security screws- M4 to suit CMDH only.