

RMW5

WEDGE HOUSINGS



Recess mounted wedge housing.

Interior recess mounted wedge housing for ceiling mount applications where vandalism is likely.

The RMW5 is manufactured from powder coated zinc plated steel while the RMW5SS is the stainless steel alternative. The enclosure offers a single keylock and dual captive security screw access. The RMW5 & RMW5SS are large attractive housings that are weatherproof and highly vandal, corrosive and tamper resistant.

The key features of the RMW5 are the range of camera adjustments and the inbuilt ceiling fastening system. Ceiling cutout dimensions measure at 212mm (W) x 380mm (L).

OPTIONS

Recess mount only.

Refer to housing Dimensions on page 44.

APPLICATIONS

Corridors, entrances and lower height applications where dome enclosures may prove to be vulnerable to attack.

SPECIFICATIONS

Construction

RMW5- 2.5mm zinc plated steel body and 2.0mm stainless steel base.
RMW5SS- 2.0mm 304 grade stainless steel and 2.0mm stainless steel base.

Finish

Mossvale sands (light beige) polyester powder coat.

Lens

6.0mm polycarbonate.

Access

4 x 6.0mm stainless steel security screws plus one Selectrix coin keylock as standard. Optional bi-lock high security key lock.

Cable Entry

2 x 20mm entries.

Max. Camera Size

265mm.

Weight

RMW5- 9.55kg.

RMW5SS- 8.0kg.

C
RMW5

C
RMW5SS

PART NUMBER

DESCRIPTION

RMW5

Zinc plated steel recessed mount wedge housing.

RMW5SS

Stainless steel recessed mount wedge housing.